



BURLINGHAM
SPORTS

Attaching padded seat to Trunk

Provided = 8 #6 x 1" Flat head Philip Screws.

- 1) Two people are needed to attach the seat.
- 2) From the back outside of the trunk, place the padded seat on the top of the trunk in the correct position.
- 3) One person needs to hold the seat onto the lid as they open the lid to a 90' angle, holding the seat with two hands against the top snugly.
- 4) The second person, from the inside of the lid, using an electric screw gun will drive the screws through the 8 cone shaped recesses into the wood underside of the seat.
- 5) Both people must work together to accomplish this. One person holding firmly and the other screwing in the screws. The person holding must apply pressure in the locations that the screw is being installed.

4575 Danito Court Chino, CA 91710
Phone 909-590-7774 e-mail: sales@burlinghamsports.com



BURLINGHAM
SPORTS

Attaching padded seat to Trunk

Provided = 8 #6 x 1" Flat head Philip Screws.

- 6) Two people are needed to attach the seat.
- 7) From the back outside of the trunk, place the padded seat on the top of the trunk in the correct position.
- 8) One person needs to hold the seat onto the lid as they open the lid to a 90' angle, holding the seat with two hands against the top snugly.
- 9) The second person, from the inside of the lid, using an electric screw gun will drive the screws through the 8 cone shaped recesses into the wood underside of the seat.
- 10) Both people must work together to accomplish this. One person holding firmly and the other screwing in the screws. The person holding must apply pressure in the locations that the screw is being installed.

4575 Danito Court Chino, CA 91710
Phone 909-590-7774 e-mail: sales@burlinghamsports.com